

Exercise 3: Solution

12DL: Prof. Dai

ImageFolderDataset: __len__()

```
def len (self):
 length = None
 # TODO:
                          #
 # Return the length of the dataset (number of images)
 length = len(self.images)
 #
           FND OF YOUR CODE
                          #
 return length
```

I2DL: Prof. Dai

ImageFolderDataset: __getitem__()

```
def __getitem__(self, index):
   data_dict = None
   # TODO:
   # create a dict of the data at the given index in your dataset
   # The dict should be of the following format:
   # {"image": <i-th image>,
   # "label": <label of i-th image>}
   # Hints:
      - use load image as numpy() to load an image from a file path
      - If applicable (Task 4: 'Transforms and Image Preprocessing'),
        make sure to apply self.transform to the image:
        image transformed = self.transform(image)
   label = self.labels[index]
   path = self.images[index]
   image = self.load_image_as_numpy(path)
   if self.transform is not None:
      image = self.transform(image)
   data dict = {
      "image": image,
      "label": label,
                          END OF YOUR CODE
   return data dict
```

Hints:

- self.images[index] contains the full name of the image we want to retrieve (we don't want to keep all images in memory at the same time - we only read them when it's required)
- Self.labels[index] contains the label of the image we want to retrieve
- We only apply the transformation if it's not None

RescaleTransform: __call__()

```
def call (self, images):
  # TODO:
  # Rescale the given images:
    - from (self. data min, self. data max)
   to (self.min, self.max)
  images = images - self. data min # normalize to (0, data max-data min)
  images /= (self._data_max - self._data_min) # normalize to (0, 1)
  images *= (self.max - self.min) # norm to (0, target max-target min)
  images += self.min # normalize to (target min, target max)
  FND OF YOUR CODE
  return images
```

12DL: Prof. Dai

compute_image_mean_and_std()

```
def compute image mean and std(images):
   .....
  Calculate the per-channel image mean and standard deviation of given images
  :param images: numpy array of shape NxHxWxC
     (for N images with C channels of spatial size HxW)
  :returns: per-channels mean and std; numpy array of shape C
  mean, std = None, None
  # TODO:
  # Calculate the per-channel mean and standard deviation of the images #
  # Hint: You can use numby to calculate mean and standard deviation
  mean = np.mean(images, axis=(0, 1, 2))
  std = np.std(images, axis=(0, 1, 2))
  END OF YOUR CODE
  return mean, std
```

12DL: Prof. Dai

Dataloader: __len__()

```
def len (self):
  length = None
  # TODO:
  # Return the length of the dataloader
  # Hint: this is the number of batches you can sample from the dataset. #
  # Don't forget to check for drop last!
  if self.drop last:
    length = len(self.dataset) // self.batch size
  else:
    length = int(np.ceil(len(self.dataset) / self.batch size))
  #
                 END OF YOUR CODE
  return length
```

I2DL: Prof. Dai

Dataloader: __iter__()

```
__iter__(self):
# TODO:
# Define an iterable function that samples batches from the dataset.
# Each batch should be a dict containing numpy arrays of length
# batch_size (except for the last batch if drop_last=True)
# Hints:
# - np.random.permutation(n) can be used to get a list of all
     numbers from 0 to n-1 in a random order
  - To load data efficiently, you should try to load only those
     samples from the dataset that are needed for the current batch.
     An easy way to do this is to build a generator with the yield
     keyword, see https://wiki.python.org/moin/Generators
   - Have a look at the "DataLoader" notebook first. This function is
     supposed to combine the functions:
      - combine batch dicts
      - batch_to_numpy
       - build batch iterator
     in section 1 of the notebook.
def combine_batch_dicts(batch):
   Combines a given batch (list of dicts) to a dict of numpy arrays
   :param batch: batch, list of dicts
       e.g. [{k1: v1, k2: v2, ...}, {k1:, v3, k2: v4, ...}, ...]
   :returns: dict of numpy arrays
       e.g. {k1: [v1, v3, ...], k2: [v2, v4, ...], ...}
   batch_dict = {}
   for data_dict in batch:
       for key, value in data_dict.items():
          if key not in batch_dict:
              batch_dict[key] = []
          batch dict[kev].append(value)
   return batch_dict
```

Hints:

We create two helper functions: one for merging a batch of dictionaries as well as a convenient way to convert those dictionaries to numpy arrays which we will then feed to our networks later.

Dataloader: __iter__()

```
def batch_to_numpy(batch):
    """Transform all values of the given batch dict to numpy arrays"""
    numpy batch = {}
    for key, value in batch.items():
        numpy batch[key] = np.array(value)
   return numpy batch
if self.shuffle:
    index iterator = iter(np.random.permutation(len(self.dataset)))
else:
    index iterator = iter(range(len(self.dataset)))
batch = []
for index in index iterator:
   batch.append(self.dataset[index])
    if len(batch) == self.batch size:
        vield batch to numpy(combine batch dicts(batch))
        batch = []
if len(batch) > 0 and not self.drop last:
    yield batch to numpy(combine batch dicts(batch))
```

Hints:

- Shuffling is implemented here using numpy's random permutation but there are multiple possible solutions
- We iterate over the dataset and use yield to properly invoke our iterator
- Finally we have to check for the last batch size in order to account for "drop_last".

Questions? Piazza 😊